



**PALUX**  
KITCHENS WITH CONCEPT

## BISTROLINE GRILL-/GRIDDLE PLATE 600

### Plus points at a glance:

- Grill-/Griddle Plate ½ grooved/smooth, 2 heating zones
- Seamlessly deep drawn top section with weld in **special steel roasting plate**
- Pressed on heating elements for optimum energy transmission
- **Integrated temperature sensors** and safety temperature limiters
- Control range between 100 - 250 °C
- **Best roasting and browning results**
- Drain with Teflon plug
- **40 mm diameter outlet** to the front with safety lock
- Large fat drip container (approx. 1 litre capacity)

### Optional:

- Case folded up at back

## Specifications

|                           |                  |
|---------------------------|------------------|
| Ordre number              | 882630           |
| Dimensions (L x W x H) mm | 600 x 650 x 270  |
| Total connected load kW   | 8,0              |
| Voltage V/Hz              | 400 V 3 50/60 Hz |
| Direct heat mission kW    | 2,64             |
| Latent heat mission kW    | 3,20             |
| Steam emission kg/h       | 3,76             |
| Fry top (L x W) mm        | 508 x 509        |
| Heating zones kW          | 2x 4,0           |
| Range of temperature °C   | 100 - 250        |

*We reserve the right to make technical changes.*