



EVO700 ELECTRIC FRYERS - 2X5 LT

FUNCTIONAL AND CONSTRUCTION FEATURES

- ◆ Tilting incoloy armoured high efficiency heating elements located inside the well.
- ◆ Working temperature from 105°C to 185°C.
- ◆ Overheat safety thermostat.
- ◆ All models have right-angled side edges to allow flush-fitting joins between units, eliminating gaps and possible dirt traps.
- ◆ One piece pressed worktop in 1,5mm stainless steel with smooth, rounded corners.
- ◆ Front panel in stainless steel with Scotch Brite finish.
- ◆ Oil drainage via a tap with push and turn safety mechanism, located on the front panel of the unit.
- ◆ IPX4 water protection.
- ◆ The special design of the control knobs and bezels guarantees against water infiltration.
- ◆ Main connections can be via the rear of the unit.

- ◆ Access to all components from the front.
- ◆ All models can easily be mounted on open base cupboards or bridging supports.
- ◆ All top models provided with service duct to facilitate installation.

TECHNICAL DATA		
CHARACTERISTICS	MODELS	
	Z7FRED2A00 372074	Z7FRED2A0N 372139
Power supply	Electric	Electric
External dimensions - mm		
width	400	400
depth	700	700
height	250	250
N° of wells	2	2
Usable well dimensions - mm		
width	110	110
depth	420	420
height	235	235
Thermostatic	●	●
Temperature limiter	●	●
Maximum Well Capacity -lt	4, 5	4, 5
Power - kW		
installed-electric	9	9
Net weight - kg.	20	20
Supply voltage	400 V, 3N, 50/60	230 V, 3, 50/60
INCLUDED ACCESSORIES		
2 BASKETS FOR 2X5 LT AND 7 LT FRYERS	1	1