



PALUX DISHWASHERS GSC 600 / STANDARD MODEL

KITCHENS WITH CONCEPT

The PALUX series GSC 600 dishwashing systems form the basis of an economically sensible washing organisation with best washing results.

The PALUX series GSC 600 dishwashing machines with an hourly output of 1080 plates or 1200 cups is particularly recommended for medium and large catering organisations.

Advantages at a glance:

- **3 basic programmes** of 60, 120, 240 seconds **and a long programme for stubborn dirt**
- Basket size 500 x 500 mm
- **Rotating washing and rinsing system**, robust, rotation wash arms made from CNS, no areas missed
- **Dual surface strainer system** with area and pump strainer for optimum filtering of the washing suds and **low water and cleaning agent consumption**
- **Water level indicator** in the washing tank with automatic topping up if water is lost



PALUX DISHWASHERS GSC 600 / STANDARD MODEL
KITCHENS WITH CONCEPT

Specifications

Ordre number	850497
Dimensions (L x W x H) mm	620 x 703 x 1425
Height with hood open mm	1892
Total connected load kW	11,6
Voltage V/Hz	400V, 3N, 50 Hz
Theoretical washing output baskets/h	60
Basket size mm	500 x 500
Quantity of washing programs	4
Program duration in seconds	60 / 120 / 240
Dish module height mm	410
Tank/ boiler content litres	24/7
Pumping capacity kW	0,9
Heater tank and boiler kW	1,6 & 9,0
Water flow temperature °C	max. 60
Water consumption/ washing phase litres	2,5 - 5,0
Water drain Ø mm	32
Water supply	R 3/4" pressure hose
Dynamic water pressure	2,5 - 6

We reserve the right to make technical changes.