



## **PALUX** KITCHENS WITH CONCEPT DISHWASHERS GSC 700 / STANDARD MODEL

The series GSC 700 is a washing powerhouse. Anywhere where output and a higher standard are prerequistes and where a superior class of equipment is in demand. The GSC 700 as a push through or corner model. With an hourly rate of 1200 plates or 1500 cups, it is ideal for the larger catering organisations.

## Advantages at a glance:

- 3 basic programmes of 60, 120, 240 seconds and a long programme for stubborn dirt ensure best washing results
- The large standard basket of 560 x 560 mm provides plenty of space for small and small plates and GN 1/1 trays
- The robust dual wash arm ensures double washing power, short washing times and best washing results
- The **dual area strainer system** for large particles, for dual filtering of the washing suds and low water and cleaning agent consumption
- The dual pumping system ensures that the washing suds are circulated twice
- Optimum handling from precisely balanced, feather light hood
- Water level indicator in the washing tank with automatic topping up if water is lost
- Deep drawn internal tank compartment with large radii and removable washing system facilitates cleaning and ensure hygiene

## **Optional:**

- Automatic measuring into dosis of cleaning agent







## Specifications

Ordre number	852260
Dimensions (L x W x H) mm	705 x 795 x 1540
Height with hood open mm	1960
Total connected load kW	16,2
Voltage V/Hz	400V, 3N, 50 Hz
Theoretical washing output baskets/h	60
Basket size mm	560 x 560
Quantity of washing programs	4
Program duration in seconds	60 / 120 / 240
Dish module height mm	425
Tank/ boiler content litres	60/12
Pumping capacity kW	2x 0,9
Heater tank and boiler kW	4,0 & 14,4
Water flow temperature °C	max. 60
Water consumption/ washing phase litres	3 - 5
Water drain Ø mm	40
Water supply	R 3/4" pressure hose
Dynamic water pressure	2,5 - 6

We reserve the right to make technical changes.