



PALUX
KITCHENS WITH CONCEPT

DISHWASHERS GSD 501-N with cleaning agent dosage

PALUX Dishwashers of the GSD 500-N series, as a push-through model or corner model are recommended as an entrance model particularly **for smaller to medium catering business**

Advantages at a glance:

- Fully automatic operation with **3 standard washing programs**: 60 / 90 / 120 seconds
- 2 special programmes:
 - Practical **self-cleaning programme** for everyday cleaning
 - **Intensive programme** for stubbornly dirty dishes
- **Completely double walled execution** for low noise levels and few heat emissions
- **Optimum filtering of washing lye** by the micro filter system - washing lye is constantly being filtered during the rinsing cycle.
- Built in rinse aid dosing device
- The smoothly lifting hood can be opened **without big force** from every position
- The internal tank heating provides **perfect rinsing temperature**
- **Easy cleaning of the seamlessly deep drawn tank** interior thanks to rounded corners
- The integrated diagnosis system indicates service information in the display
- **Query of rinse and washing temperatures** is possible via the display
- The best cleaning result, the easiest operation and the highest reliability



PALUX
KITCHENS WITH CONCEPT

DISHWASHERS GSD 501-N
with cleaning agent dosage

Specifications

Ordre number	883635
Dimensions (L x W x H) mm	633 x 755 x 1570
Total connected load kW	8,7
Voltage V/Hz	400V, 2N, 50 Hz
Theoretical washing output baskets/h	60
Basket size mm	500 x 500
Quantity of washing programs	3 + 2 special programs
Program duration in seconds	60 / 120 / 240
Dish module height mm	465
Tank/ boiler content litres	22/6
Pumping capacity kW	0,7
Heater tank and boiler kW	0,21 & 8,0
Water flow temperature °C	15 - 50
Water consumption/ washing phase litres	2,7
Water drain Ø mm	32
Water supply	R 3/4" pressure hose
Dynamic water pressure	2,5 - 6

We reserve the right to make technical changes.