# Model: **A140/2NV**

Code: A141401007

### **Exterior/interior finishing:**

- Stainless steel AISI 304 18/10
- Back in galvanised steel

### **Insulation:**

• 75 mm thickness - CFC/HCFC free

### **Cover evaporator:**

• Removable in stainless steel AISI 304 Cr-Ni 18/10

### Internal racks and slides:

• Stainless steel AISI 304 18/10

### **Inner corners:**

• Rounded cornes ensuring maximum hygiene Feet:

### • Stainless steel AISI 304 adjustable 100-150 mm

### • Self-closing, reversible with 105° dwell Door handle:

• In PVC

### Door gasket:

• Magnetic, easy to replace





















• Dimensions	1480×815×2085 mm
Packing dimensions	1500×850×2250 mm
Net weight	245 Kg
Gross capacity	1400 lt
Temperature range	0°+10°C
Cooling capacity	668 W*
Standard connection	230 V - 50 Hz
Total rate	653 W - 3,6 A
Cooling gas	R404a
Standard equipment	N. 6 plastic coated shelves - GN2/1
	Key lock
• *Evap10°C cond. 54,4°C	




Plastic coated shelf GN 650×530 mm Code O221650530





Code O261650530





Pair of slides type C - 605 mm Code O121160520



Stainless steel drawer for cabinet Master 700-H150 mm Code L313007304



Graphic temperature recorder -10°+40°C Code 0841100020







## Catering

### Depth 815 mm

Coldline made major investments in design research, becoming a leader in technology and innovation. Each cabinet marked with the FSSsymbol is equipped with a refrigeration system independent of the structure, which provides improved flexibility and service.



### **FSS • FAST SERVICE SYSTEM**

- You can change the intended use of an appliance, a freezer into a chiller - and the other way around - even after years of installation.
- You can extend the life of a refrigeration cabinet by replacing its old refrigeration system with a new one.
- Maintenance and service are simple, guick and do not require specialised personnel.



# -SS • Fast Service System

## **NO-COMPROMISE QUALITY STEEL**

AISI 304 18/10 is a high quality steel. Its stability guarantees good-looking and durable products, ensuring maximum hygiene and corrosion resistance over time.



### **INSULATION THICKNESS**

The 75 mm thick insulation ensures lower heat loss, reduced work of the compressor, therefore lower energy consumption.



### **INTELLIGENT DEFROST**

Intelligent defrost changes according to the actual presence of frost. The system runs for the minimum time required.



### **EVAPORATION SYSTEM**

The automatic evaporation of condensing water is activated only in the presence of water produced as a result of a defrost cycle.




### **CONSTANT TEMPERATURE**


The fans stop when the door is opened to reduce temperature changes and consequently reduce the work of the compressor.



### **ASPERA COMPRESSORS**

Aspera compressors reduce energy consumption by 15% and acoustic impact by 5 dBA.





A POWER SUPPLY CABLE OUTLET

**G** RACKS PITCH









• Trade mark:	Coldline
• Model:	A140/2NV
• Design:	Upright cabinet
• Energy efficiency class :	F
• Energy efficiency index :	93,1
• Net volume positive/negative:	870 -
• Climate class:	4 (30°C-55% r.h.)
• Energy consumption over 24 hours (E24h):	5,20
Annual energy consumption in kWh:	1898
• Cooling gas:	R404a

