Catering

Depth 815 mm

Model: A140/2MB Code:

Exterior/interior finishing: • Stainless steel AISI 304 18/10 • Back in galvanised steel Insulation: • 75 mm thickness - CFC/HCFC free **Cover evaporator:** • Removable in stainless steel AISI 304 Cr-Ni 18/10 Internal racks and slides: Stainless steel AISI 304 18/10 **Inner corners:** • Rounded cornes ensuring maximum hygiene Feet: • Stainless steel AISI 304 adjustable 100-150 mm Door: • Self-closing, reversible with 105° dwell Door handle: • Stainless steel AISI 304 Cr-Ni 18/10 Door gasket: Magnetic, easy to replace

Cabinet Master Combi 1400 lt -2°+8°/-18°-22°C 2 doors



& coldline



Catering

Depth 815 mm

Cabinet Master Combi 1400 lt -2°+8°/-18°-22°C 2 doors

Coldline made major investments in design research, becoming a leader in technology and innovation. Each cabinet marked with the FSSsymbol is equipped with a refrigeration system independent of the structure, which provides improved flexibility and service.





FSS • FAST SERVICE SYSTEM

over time.

time required.

• You can change the intended use of an appliance, a freezer into a chiller - and the other way around - even after years of installation.

• You can extend the life of a refrigeration cabinet by replacing its old refrigeration system with a new one.

NO-COMPROMISE QUALITY STEEL

AISI 304 18/10 is a high quality steel. Its stability

ensuring maximum hygiene and corrosion resistance

Intelligent defrost changes according to the actual

presence of frost. The system runs for the minimum

guarantees good-looking and durable products,

 Maintenance and service are simple, quick and do not require specialised personnel.



INSULATION THICKNESS

The 75 mm thick insulation ensures lower heat loss, reduced work of the compressor, therefore lower energy consumption.

EVAPORATION SYSTEM

The automatic evaporation of condensing water is activated only in the presence of water produced as a result of a defrost cycle.



CONSTANT TEMPERATURE

1480

INTELLIGENT DEFROST



The fans stop when the door is opened to reduce temperature changes and consequently reduce the work of the compressor.



ASPERA COMPRESSORS

1480


Aspera compressors reduce energy consumption by 15% and acoustic impact by 5 dBA.


(A)

ក្ល

190

& coldlir





815

(A) POWER SUPPLY CABLE OUTLET

G RACKS PITCH



Cold Line S.r.I. • Via E. Mattei, 38 • 35038 Torreglia • Padova - Italy • www.coldline.it • info@coldline.it

Focus

Technical drawing